

# PO SITE DESIGN | LENGTH OF PARKING ALONG STREET

## Standard: 60 ft

- The current PO standard is that parking lots shall be limited to not more than sixty (60) feet of street frontage. This allows for a two-way drive aisle and parking on either side of the aisle.



26th St W & Hennepin Ave

What do you like about this option?



27th St W & Hennepin Ave



Fremont Ave A & Hennepin Ave

What do you not like?



Between 27th & 28th St W along Hennepin Ave

## Potential: 40 ft

- A change from the PO standard of 60 feet is a potential. A maximum length of 40 feet could be considered. This would allow for a two-way drive aisle and one side of parking.



Between 29th & 28th St W along Lyndale Ave

What do you like about this option?



22nd St W & Hennepin Ave



Between Lake & 29th St W along Lyndale Ave

What do you not like?



26th St W & Lyndale Ave



Lake Street & Dupon Ave S

## Potential: None

- A change from the PO standard of 60 feet is a potential. Not allowing parking to front the major (Hennepin, Lyndale, Lake) street could be considered. This would allow for a two-way drive aisle to access parking in the rear or internal to a building.



Between Emerson & Fremont Ave S along Lake Street

What do you like about this option?



Between 31st & Lake St along Hennepin Ave

What do you not like?



Between Bryant & Colfax Ave S along Lake Street