



NOTES:

- ① CATCH BASIN CASTING.
- ② ON ALL APPLICATIONS USE 1-1/4" SUMP. SUMP SHALL BE MEASURED AT CENTER OF CASTING.
- ③ SAME THICKNESS AS ADJACENT PAVEMENT OR GUTTER.
- ④ CURB INLET CASTING SHALL BE FASTENED TEMPORARILY TO FRAME CASTING WITH 2 CAP SCREWS, DURING CURB CONSTRUCTION. CAP SCREWS MUST BE REMOVED AFTER CURB HAS HARDENED.

COMPENSATE FOR TILT BY VARYING THE DEPTH OF MORTAR SEAT.
ALL REINFORCEMENT REQUIRED IS INCIDENTAL, WITH NO DIRECT PAYMENT.
ALL REBARS ARE IN ENGLISH DESIGNATIONS.
ALL REBARS ARE GRADE 60

MNDOT SPEC. REF. 2506
MNDOT 7111J
NOT TO SCALE



MINNEAPOLIS
DEPARTMENT OF PUBLIC WORKS

DRAWN: DCD

DATE: 5/03

APPROVED: HRS

DATE: 12/06

CATCH BASIN INSTALLATION

STANDARD
PLATE
NO.
SEWR-1009